

View Online at <https://aerobasegroup.com/nsn/5340-01-436-1798>

Mounting Hole Type:

Plain

First Leg Length:

2.0000 inches

Second Leg Length:

3.7600 inches

Second Leg Width:

3.2500 inches

Second Leg Corner Radius:

0.2500 inches

First Leg Hole Diameter:

Between 0.2330 inches and 0.2390 inches

Second Leg Hole Diameter:

0.1900 inches

Second Leg Distance Between Hole Centers Along Width:

2.6770 inches

Second Leg Distance Between Hole Centers Along Length:

2.7560 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.2865 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.5260 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

3.2500 inches

First Leg Corner Radius:

0.2500 inches

First Leg Distance Between Hole Centers Along Width:

2.7500 inches

First Leg Distance Between Hole Centers Along Length:

0.3750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.2500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.32 radians and 0.44 radians

Special Features:

There are two sets of inserts helical coil. The first set has four insert msde to ms21290f1-10l (.190-32unf x 19l). The final set has two inserts made to ms21209c0610l (.138-32unc x .14l)

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/16 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8825, type 2, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8825 spec.