

View Online at <https://aerobasegroup.com/nsn/5340-01-436-1798>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.0000 inches

**Second Leg Length:**

3.7600 inches

**Second Leg Width:**

3.2500 inches

**Second Leg Corner Radius:**

0.2500 inches

**First Leg Hole Diameter:**

Between 0.2330 inches and 0.2390 inches

**Second Leg Hole Diameter:**

0.1900 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.6770 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.7560 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.2865 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.5260 inches

**First Leg Thickness:**

0.2500 inches

**Second Leg Thickness:**

0.2500 inches

**First Leg Width:**

3.2500 inches

**First Leg Corner Radius:**

0.2500 inches

**First Leg Distance Between Hole Centers Along Width:**

2.7500 inches

**First Leg Distance Between Hole Centers Along Length:**

0.3750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.2500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.2500 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.32 radians and 0.44 radians

**Special Features:**

There are two sets of inserts helical coil. The first set has four insert msde to ms21290f1-10l (.190-32unf x 19l). The final set has two inserts made to ms21209c0610l (.138-32unc x .14l)

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/16 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8825, type 2, cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8825 spec.