

View Online at <https://aerobasegroup.com/nsn/5340-01-436-3384>

First Leg Length:

1.1880 inches

Second Leg Length:

Between 1.1900 inches and 1.3100 inches

Second Leg Width:

12.5000 inches

Second Leg Corner Radius:

0.2500 inches

First Leg Hole Diameter:

Between 0.2560 inches and 0.2580 inches

Second Leg Hole Diameter:

Between 0.2650 inches and 0.2720 inches

Second Leg Distance Between Hole Centers Along Width:

11.5000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.5600 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

5.6400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.5000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.5000 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

12.5000 inches

First Leg Corner Radius:

0.2500 inches

First Leg Distance From Edge To Hole Center Along Width:

6.3750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2880 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.19 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/16 federal specification single material response or qq-a-200/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, cl 2 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.