NSN 5340-01-436-3409

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-436-3409

First Leg Length:

Between 1.1900 inches and 1.3100 inches

Second Leg Length:

1.1880 inches

Second Leg Width:

12.5000 inches

Second Leg Corner Radius:

0.2500 inches

First Leg Hole Diameter:

Between 0.2560 inches and 0.2580 inches

Second Leg Hole Diameter:

Between 0.2650 inches and 0.2720 inches

Second Leg Distance Between Hole Centers Along Width:

11.5000 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

3.5600 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

5.6400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.5000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.5000 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

12.5000 inches

First Leg Corner Radius:

0.2500 inches

First Leg Distance From Edge To Hole Center Along Width:

6.3750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2880 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

NSN 5340-01-436-3409 Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
0.19 radians
Special Features:
The item is opposite of part number 3141as425-1
Material:
Aluminum alloy 6061
Material Specification:
Qq-a-200/16 federal specification single material response or qq-a-200/8 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 3, cl 2 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:
A042a0
Mil-std (military Standard):
Mil-a-8625 spec.