

View Online at <https://aerobasegroup.com/nsn/5340-01-439-2933>

First Leg Length:

Between 36.0 millimeters and 40.0 millimeters

Second Leg Length:

Between 118.0 millimeters and 122.0 millimeters

Second Leg Width:

Between 278.0 millimeters and 282.0 millimeters

Second Leg End Width:

248.0 millimeters

First Leg Hole Diameter:

Between 6.6 millimeters and 7.0 millimeters

Second Leg Hole Diameter:

Between 6.5 millimeters and 7.5 millimeters

Second Leg Distance Between Hole Centers Along Width:

100.0 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

20.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

55.0 millimeters

First Leg Thickness:

1.905 millimeters

Second Leg Thickness:

1.905 millimeters

First Leg Width:

Between 239.0 millimeters and 241.0 millimeters

First Leg Distance Between First And Second Hole Centers Along Width:

Between 119.0 millimeters and 121.0 millimeters

First Leg Distance Between Second And Third Hole Centers Along Width:

Between 119.0 millimeters and 121.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 14.0 millimeters and 18.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 14.0 millimeters and 18.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 4.0 radians and 8.0 radians

Second Leg Chamfer Angle:

Between 42.0 degrees and 48.0 degrees

Material:

Steel comp 1009

Material Specification:

Astm-a-569 assn standard single material response or astm-a-366 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0