

View Online at <https://aerobasegroup.com/nsn/5340-01-439-2947>

First Leg Length:

Between 52.0 millimeters and 56.0 millimeters

Second Leg Length:

Between 58.2 millimeters and 62.0 millimeters

Second Leg Width:

Between 428.0 millimeters and 432.0 millimeters

Second Leg End Width:

418.0 millimeters

First Leg Hole Diameter:

Between 9.5 millimeters and 10.5 millimeters

Second Leg Hole Diameter:

Between 9.5 millimeters and 10.5 millimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

165.0 millimeters

Second Leg Distance Between Second And Third Hole Centers Along Width:

195.0 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

30.4 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

19.8 millimeters

First Leg Thickness:

3.429 millimeters

Second Leg Thickness:

3.429 millimeters

First Leg Width:

Between 288.0 millimeters and 292.0 millimeters

First Leg End Width:

178.0 millimeters

First Leg Distance Between First And Second Hole Centers Along Width:

165.0 millimeters

First Leg Distance Between Second And Third Hole Centers Along Width:

75.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

30.4 millimeters

First Leg Distance From Edge To Hole Center Along Length:

18.0 millimeters

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 6.0 radians and 8.0 radians

First Leg Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

Second Leg Chamfer Angle:

Between 43.0 degrees and 47.0 degrees

Material:

Steel comp 1009

Material Specification:

Astm-a-366 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0