# NSN 5340-01-439-5309

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-439-5309

# **Thread Class:**

2b left internal (includes through thread)

## **Thread Direction:**

Right-hand left internal (includes through thread)

# Thread Length:

0.2200 inches and 0.2300 inches left internal (includes through thread)

#### Length:

Between 0.1620 inches and 0.1680 inches

## **Cross-sectional Shape:**

Hexagon

Width Across Flats:

0.2500 inches

Thready Qty Per Inch (tpi):

32 left internal (includes through thread)

#### **Thread Size:**

0.1640 inches left internal (includes through thread)

#### **Right Projection Diameter:**

Between 0.1850 inches and 0.1880 inches

# **Right Projection Length:**

Between 0.2200 inches and 0.2300 inches

# Material:

Steel comp 304

#### Material Specification:

Qq-a-763 federal specification single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-f-14072-e300 military specification single treatment response

#### Style Designator:

Projection one end

## **Thread Series Designator:**

Unc left internal (includes through thread)

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A08900

# Mil-std (military Standard):

Mil-f-14072-e300 spec.