

View Online at <https://aerobasegroup.com/nsn/5340-01-440-1350>

Mounting Hole Type:

Plain

First Leg Length:

Between 4.800 inches and 4.940 inches

Second Leg Length:

Between 1.700 inches and 1.800 inches

End Application:

Alternator, assembly 11b251005

Second Leg Width:

Between 0.800 inches and 0.840 inches

First Leg Slot Length:

Between 2.600 inches and 2.640 inches

First Leg Slot Width:

Between 0.380 inches and 0.460 inches

Second Leg Hole Diameter:

Between 0.430 inches and 0.450 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.420 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

Center Section Height:

Between 2.230 inches and 2.260 inches

Center Section Width:

Between 0.800 inches and 0.840 inches

Center Section Thickness:

0.250 inches

First Leg Width:

Between 0.800 inches and 0.840 inches

First Leg Distance From Edge To Hole Center Along Width:

0.420 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg End Radius:

Between 0.480 inches and 0.520 inches

Second Leg End Radius:

Between 0.480 inches and 0.520 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.230 radians and 0.270 radians

Second Leg Angle:

Between 0.230 radians and 0.270 radians

Product Name:

Alternator bracket

Material:

Steel comp 1020 or steel comp 1025

Material Specification:

Ams-5046 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0