

View Online at <https://aerobasegroup.com/nsn/5340-01-440-1834>

First Leg Length:

Between 1.6900 inches and 1.8100 inches

Second Leg Length:

Between 5.6900 inches and 5.9300 inches

Second Leg Width:

Between 4.6900 inches and 4.8100 inches

Second Leg Corner Radius:

Between 0.3800 inches and 0.6200 inches

First Leg Hole Diameter:

Between 0.4700 inches and 0.5300 inches

Second Leg Hole Diameter:

0.2500 inches

Second Leg Distance Between Hole Centers Along Width:

Between 2.7200 inches and 2.7800 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.9600 inches and 1.0600 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.5600 inches and 0.6800 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

Between 4.6900 inches and 4.8100 inches

First Leg Distance Between Hole Centers Along Width:

Between 2.7200 inches and 2.7800 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.9400 inches and 1.0600 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.4400 inches and 0.5600 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.46 radians and 0.56 radians

Material:

Steel comp 1006 or steel comp 1008 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016

Material Specification:

Astm-a-36 assn standard single material response or astm-a-283 assn standard single material response or astm-a-827 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0