

View Online at <https://aerobasegroup.com/nsn/5340-01-442-3381>

First Leg Length:

35.0 millimeters

Second Leg Length:

58.0 millimeters

Second Leg Width:

127.0 millimeters

First Leg Hole Diameter:

Between 0.7 millimeters and 2.3 millimeters

Second Leg Distance Between Hole Centers Along Width:

Between 88.3 millimeters and 88.9 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

19.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

22.0 millimeters

Second Leg Slot Length:

Between 23.2 millimeters and 24.8 millimeters

Second Leg Slot Width:

Between 11.9 millimeters and 12.3 millimeters

First Leg Thickness:

3.03 millimeters

Second Leg Thickness:

3.03 millimeters

First Leg Width:

127.0 millimeters

First Leg End Width:

41.73 millimeters

First Leg Distance Between Hole Centers Along Width:

Between 30.7 millimeters and 31.3 millimeters

First Leg Distance From Edge To Hole Center Along Width:

48.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

23.1 millimeters

First Leg Style:

Corner radius w/ tongue

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

Material:

Steel comp 410 or steel uns k42544 or steel comp 1137 or steel uns k01507 or steel uns k02500

Material Specification:

Astm-a-366 assn standard single material response or astm-a-109 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0