

View Online at <https://aerobasegroup.com/nsn/5340-01-442-3381>

**First Leg Length:**

35.0 millimeters

**Second Leg Length:**

58.0 millimeters

**Second Leg Width:**

127.0 millimeters

**First Leg Hole Diameter:**

Between 0.7 millimeters and 2.3 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

Between 88.3 millimeters and 88.9 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

19.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

22.0 millimeters

**Second Leg Slot Length:**

Between 23.2 millimeters and 24.8 millimeters

**Second Leg Slot Width:**

Between 11.9 millimeters and 12.3 millimeters

**First Leg Thickness:**

3.03 millimeters

**Second Leg Thickness:**

3.03 millimeters

**First Leg Width:**

127.0 millimeters

**First Leg End Width:**

41.73 millimeters

**First Leg Distance Between Hole Centers Along Width:**

Between 30.7 millimeters and 31.3 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

48.0 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

23.1 millimeters

**First Leg Style:**

Corner radius w/ tongue

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**Material:**

Steel comp 410 or steel uns k42544 or steel comp 1137 or steel uns k01507 or steel uns k02500

**Material Specification:**

Astm-a-366 assn standard single material response or astm-a-109 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0