

View Online at <https://aerobasegroup.com/nsn/5340-01-443-1360>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 30.7 millimeters and 33.7 millimeters

**Second Leg Length:**

Between 42.0 millimeters and 45.0 millimeters

**Second Leg Width:**

Between 93.5 millimeters and 96.5 millimeters

**Second Leg End Width:**

56.4 millimeters

**First Leg Hole Diameter:**

Between 9.0 millimeters and 9.2 millimeters

**Second Leg Hole Diameter:**

Between 7.0 millimeters and 8.0 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

75.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

10.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

30.0 millimeters

**First Leg Thickness:**

3.048 millimeters

**Second Leg Thickness:**

3.048 millimeters

**First Leg Width:**

Between 93.5 millimeters and 96.5 millimeters

**First Leg End Width:**

25.0 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

47.5 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

16.4 millimeters

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 1.0 radians and 3.0 radians

**First Leg Chamfer Angle:**

Between 16.0 radians and 22.0 radians

**Second Leg Chamfer Angle:**

Between 2.0 radians and 6.0 radians

**Material:**

Steel comp 410 or steel uns k42544 or steel comp 1009

**Material Specification:**

Astm-a-366 assn standard single material response or astm-a-569 assn standard single material response

**Surface Treatment:**

Phosphate zinc or paint

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0