

View Online at <https://aerobasegroup.com/nsn/5340-01-443-1360>

Mounting Hole Type:

Plain

First Leg Length:

Between 30.7 millimeters and 33.7 millimeters

Second Leg Length:

Between 42.0 millimeters and 45.0 millimeters

Second Leg Width:

Between 93.5 millimeters and 96.5 millimeters

Second Leg End Width:

56.4 millimeters

First Leg Hole Diameter:

Between 9.0 millimeters and 9.2 millimeters

Second Leg Hole Diameter:

Between 7.0 millimeters and 8.0 millimeters

Second Leg Distance Between Hole Centers Along Width:

75.0 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

10.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

30.0 millimeters

First Leg Thickness:

3.048 millimeters

Second Leg Thickness:

3.048 millimeters

First Leg Width:

Between 93.5 millimeters and 96.5 millimeters

First Leg End Width:

25.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

47.5 millimeters

First Leg Distance From Edge To Hole Center Along Length:

16.4 millimeters

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 1.0 radians and 3.0 radians

First Leg Chamfer Angle:

Between 16.0 radians and 22.0 radians

Second Leg Chamfer Angle:

Between 2.0 radians and 6.0 radians

Material:

Steel comp 410 or steel uns k42544 or steel comp 1009

Material Specification:

Astm-a-366 assn standard single material response or astm-a-569 assn standard single material response

Surface Treatment:

Phosphate zinc or paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0