

View Online at <https://aerobasegroup.com/nsn/5340-01-445-5373>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.091 inches

**Second Leg Length:**

0.075 inches

**End Application:**

F-15i

**Second Leg Width:**

1.000 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.220 inches and 0.230 inches

**Second Leg Hole Diameter:**

Between 0.129 inches and 0.134 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.050 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.150 inches

**First Leg End Radius:**

0.310 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Bracket assembly, clamp support, offset, lightweight, clip nut

**Special Features:**

Item has lockwire hole, diameter 0.094plus 0.005 in.; bracket is intended to attached w/rivets; has clip nut p/n st3m523c3m and has conventiona (not inverted) installation

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-250/5 federal specification single material response

**Surface Treatment:**

Primer and chromate

**Surface Treatment Specification:**

Mil-p-23377 military specification 1st treatment response and mil-c-5541 military specification 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-23377 spec.