

View Online at <https://aerobasegroup.com/nsn/5340-01-445-6927>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.1200 inches and 1.2900 inches

Second Leg Length:

Between 2.1600 inches and 2.3400 inches

Second Leg Width:

Between 2.3500 inches and 2.4100 inches

Second Leg Corner Radius:

Between 0.0900 inches and 0.1500 inches

First Leg Slot Length:

Between 0.3500 inches and 0.4100 inches

First Leg Slot Width:

Between 0.2660 inches and 0.2960 inches

Second Leg Hole Diameter:

Between 0.2010 inches and 0.2100 inches

Second Leg Distance Between Hole Centers Along Width:

1.5000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.4400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.6200 inches

First Leg Thickness:

0.0620 inches

Second Leg Thickness:

0.0620 inches

First Leg Width:

0.1370 inches

First Leg Corner Radius:

Between 0.0900 inches and 0.1500 inches

First Leg Distance Between Hole Centers Along Width:

1.0250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.8450 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.2660 inches and 2.2960 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.0900 radians and 0.2100 radians

Material:

Steel comp 1009

Material Specification:

Astm-a-569 assn standard single material response or astm-a-366 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0