## NSN 5340-01-445-8291

Swivel Caster - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5340-01-445-6291
Center To Center Distance Between Bolt Holes Along Width:
2.625 inches
Center To Center Distance Between Bolt Holes Along Length:
3.625 inches
Wheel Quantity:
1
Safe Operating Load Rating:
500.0 pounds
Material And Location:
Steel plate err-100 err-100
Surface Treatment And Location:
Cadmium plate or zinc plated plate or painted plate or lacquer plate or enamel plate
Wheel Type:
Built up
Wheel Diameter:
4.000 inches
Effective Height:
5.562 inches
Features Provided:
Swivel lubrication fitting
Plate Style:
Rectangular
Wheel Bearing Type:
Roller or ball
Swivel Bearing Type:
Annular ball
Swivel Bearing Arrangement:
Two row or two level
Tread Width:
2.000 inches
Caster Plate Length:
5.500 inches
Caster Plate Width:
5.000 inches
Caster Plate Mounting Hole Diameter:
0.375 inches
Special Features:
No surface finish on aluminum casters; optional mounting plate hole spacing 3.000 in. By 3.000 in.
Style Designator:
Swivel offset
Specification Or Standard:

A group and 2 type and 4 class and 1 style

## NSN 5340-01-445-8291

Swivel Caster - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A25600