NSN 5340-01-446-0608

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-446-0608
Mounting Hole Type:
Plain
Second Leg Width:
1.500 inches
Second Leg Corner Radius:
0.250 inches
Second Leg Hole Diameter:
Between 0.220 inches and 0.230 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Thickness:
0.050 inches
Second Leg Thickness:
0.050 inches
Center Section Height:
0.500 inches
Center Section Width:
1.500 inches
Center Section Thickness:
0.050 inches
First Leg Width:
1.500 inches
First Leg Corner Radius:
0.250 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
No hole
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Special Features:
Attached with rivets; requires clip nut in center hole position; intended for support of wire bundles only. Bracket same as part number

9m672c2l except has 3 holes and clip moved to center hole

NSN 5340-01-446-0608

Double Angle Bracket - Page 2 of 2



Material:
Aluminum alloy 2024
Material Specification:
Qq-a-250/5, t81 federal specification single material response
Surface Treatment:
Primer and chromate
Surface Treatment Specification:
Mil-p-23377 military specification 1st treatment response and mil-c-5541 military specification 2nd treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-p-23377 spec.