

View Online at <https://aerobasegroup.com/nsn/5340-01-446-7472>

First Leg Length:

1.4400 inches

Second Leg Length:

4.8400 inches

Second Leg Width:

1.3800 inches

First Leg Hole Diameter:

Between 0.4650 inches and 0.4850 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.6250 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.3090 inches

Second Leg Slot Length:

Between 1.0950 inches and 1.1550 inches

Second Leg Slot Width:

Between 0.4540 inches and 0.4840 inches

First Leg Thickness:

0.1860 inches

Second Leg Thickness:

0.1860 inches

First Leg Width:

1.5000 inches

First Leg Corner Radius:

0.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.2500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.5090 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.09 radians

Second Leg Cutout Length:

1.1210 inches

Second Leg Cutout Width:

Between 0.4540 inches and 0.4840 inches

Material:

Steel comp 1026 or steel comp 1029 or steel comp 1030

Material Specification:

Astm-a-36 assn standard single material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Amil-std-171, 5.1.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.