

View Online at <https://aerobasegroup.com/nsn/5340-01-446-7472>

**First Leg Length:**

1.4400 inches

**Second Leg Length:**

4.8400 inches

**Second Leg Width:**

1.3800 inches

**First Leg Hole Diameter:**

Between 0.4650 inches and 0.4850 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.6250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

2.3090 inches

**Second Leg Slot Length:**

Between 1.0950 inches and 1.1550 inches

**Second Leg Slot Width:**

Between 0.4540 inches and 0.4840 inches

**First Leg Thickness:**

0.1860 inches

**Second Leg Thickness:**

0.1860 inches

**First Leg Width:**

1.5000 inches

**First Leg Corner Radius:**

0.5000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.2500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.5090 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.09 radians

**Second Leg Cutout Length:**

1.1210 inches

**Second Leg Cutout Width:**

Between 0.4540 inches and 0.4840 inches

**Material:**

Steel comp 1026 or steel comp 1029 or steel comp 1030

**Material Specification:**

Astm-a-36 assn standard single material response

**Surface Treatment:**

Phosphate zinc

**Surface Treatment Specification:**

Amil-std-171, 5.1.1 military standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.