

View Online at <https://aerobasegroup.com/nsn/5340-01-447-8958>

Mounting Hole Type:

Plain

First Leg Length:

0.750 inches

Second Leg Length:

0.910 inches

End Application:

F-15i

Second Leg Width:

1.000 inches

First Leg Hole Diameter:

Between 0.129 inches and 0.134 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.310 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

Product Name:

Bracket assembly-clamp support, offset, lightweight, clip nut

Special Features:

2nd leg has lockwire hole, diameter 0.094 pom 0.005 in.; bracket is intended to be attached w/rivets, with or without clipnuts for clamp attachment

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Surface Treatment:

Chromate and primer

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-p-23377 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.