NSN 5340-01-448-3222

Thread Class: 2b right internal

Snap-in Threaded Standoff - Page 1 of 2

As modified by material and locking featur (as applicable)



View Online at https://aerobasegroup.com/nsn/5340-01-448-3222

Thread Direction:
Right-hand right internal
Thread Length:
0.265 inches left external
Width Between Flats:
0.375 inches
Length:
4.000 inches
Thready Qty Per Inch (tpi):
32 right internal
Thread Size:
0.190 inches left external
Criticality Code Justification:
Zzzy
Right Projection Diameter:
0.190 inches
Right Projection Length:
0.374 inches
Right End Chamfer Angle:
Between 25.0 degrees and 35.0 degrees
Err Default:
Err default
Material:
Steel comp 303 standoff
Material Specification:
Stm a581 assn standard single material response standoff
Surface Treatment:
Passivate standoff
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-35, type ii federal specification single treatment response standoff
Style Designator:
Left internal and right external thread
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf left external
Departure From Cited Document:

NSN 5340-01-448-3222

Snap-in Threaded Standoff - Page 2 of 2



Reference Number Differentiating Characteristic	istics:	Character	ntiating	Diffe	Number	erence	Ref
---	---------	-----------	----------	-------	--------	--------	-----

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08900