NSN 5340-01-449-2022

Angle Bracket - Page 1 of 2

Mounting Hole Type:

View Online at https://aerobasegroup.com/nsn/5340-01-449-2022



Plain
First Leg Length:
2.4370 inches
Second Leg Length:
4.0000 inches
Second Leg Width:
12.0000 inches
First Leg Hole Diameter:
Between 0.4030 inches and 0.4100 inches
Second Leg Hole Diameter:
Between 0.4030 inches and 0.4100 inches
Second Leg Distance Between Hole Centers Along Width:
10.5000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.5000 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.5000 inches
First Leg Thickness:
0.2500 inches
Second Leg Thickness:
0.2500 inches
First Leg Width:
11.5000 inches
First Leg Distance Between Hole Centers Along Width:
10.0300 inches
First Leg Distance Between First And Second Hole Centers Along Width:
2.0300 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
5.9700 inches
First Leg Distance From Edge To Hole Center Along Width:
1.0000 inches
First Leg Distance From Edge To Hole Center Along Length:
1.2500 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes

NSN 5340-01-449-2022

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.2500 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171, 7.1.1, 7.2.1, 7.3.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.