

View Online at <https://aerobasegroup.com/nsn/5340-01-449-9717>

Mounting Hole Type:

Plain

First Leg Length:

0.7500 inches

Second Leg Length:

0.7500 inches

Second Leg Width:

1.0000 inches

Second Leg Corner Radius:

0.2500 inches

First Leg Hole Diameter:

Between 0.1290 inches and 0.1340 inches

Second Leg Hole Diameter:

Between 0.2200 inches and 0.2300 inches

Second Leg Distance Between Hole Centers Along Width:

0.5000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.2500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Thickness:

0.0500 inches

Second Leg Thickness:

0.0500 inches

First Leg Width:

1.0000 inches

First Leg Corner Radius:

0.2500 inches

First Leg Distance Between Hole Centers Along Width:

0.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.2500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.1600 radians

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.