NSN 5340-01-451-3855



Double Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-451-3855 First Leg Length: 1.500 inches Second Leg Length: 2.120 inches Second Leg Width: 1.440 inches Second Leg End Width: 1.200 inches First Leg Slot Length: Between 0.505 inches and 0.510 inches First Leg Slot Width: Between 0.473 inches and 0.478 inches Second Leg Hole Diameter: Between 0.174 inches and 0.180 inches Second Leg Distance Between Hole Centers Along Width: 1.190 inches Second Leg Distance From Edge To Hole Center Along Width: Between 0.150 inches and 0.170 inches Second Leg Distance From Edge To Hole Center Along Length: Between 0.177 inches and 0.197 inches First Leg Thickness: 0.125 inches Second Leg Thickness: 0.125 inches **Center Section Width:** 1.440 inches **Center Section Thickness:** 0.125 inches First Leg Width: 1.440 inches First Leg End Width: 0.940 inches First Leg Distance From Edge To Hole Center Along Width: 0.720 inches First Leg Distance From Edge To Hole Center Along Length: 0.750 inches First Leg Style: Chamfered ends First Leg Hole Arrangement Style:

One slot Second Leg Style: Chamfered ends

NSN 5340-01-451-3855

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Chamfer Angle:
45.0 degrees
Second Leg Chamfer Angle:
45.0 degrees
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 temper h32 federal specification single material response
Surface Treatment:
Oxide film and chromate
Surface Treatment Specification:
Mil-c-5541, cl 1a or 3 military specification 2nd treatment response
Style Designator:
Offset double angle
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.