

View Online at <https://aerobasegroup.com/nsn/5340-01-451-3855>

First Leg Length:

1.500 inches

Second Leg Length:

2.120 inches

Second Leg Width:

1.440 inches

Second Leg End Width:

1.200 inches

First Leg Slot Length:

Between 0.505 inches and 0.510 inches

First Leg Slot Width:

Between 0.473 inches and 0.478 inches

Second Leg Hole Diameter:

Between 0.174 inches and 0.180 inches

Second Leg Distance Between Hole Centers Along Width:

1.190 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.150 inches and 0.170 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.177 inches and 0.197 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Width:

1.440 inches

Center Section Thickness:

0.125 inches

First Leg Width:

1.440 inches

First Leg End Width:

0.940 inches

First Leg Distance From Edge To Hole Center Along Width:

0.720 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 temper h32 federal specification single material response

Surface Treatment:

Oxide film and chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a or 3 military specification 2nd treatment response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.