## NSN 5340-01-452-7018



Spacing Threaded Standoff - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-452-7018 **Thread Class:** 3b left internal (includes through thread) **Thread Direction:** Right-hand left internal (includes through thread) Thread Length: 0.4720 inches left internal (includes through thread) Flange Diameter: 1.2500 inches Flange Thickness: 1.0280 inches Diameter: 0.3100 inches Length: 0.4720 inches **Cross-sectional Shape:** Round Thready Qty Per Inch (tpi): 32 left internal (includes through thread) **Thread Size:** 0.1900 inches left internal (includes through thread) **Special Features:** There is a inspection hole with a dia. Of 0.062 min. And 0.070 max. Inch Material: Aluminum alloy 2024 or aluminum alloy 6061 **Material Specification:** Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-250 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Flanged **Thread Series Designator:** Unf left internal (includes through thread) Shelf Life: N/a **Unit Of Measure:** 

Fiig: A08900

No

**Demilitarization:** 

## NSN 5340-01-452-7018

Spacing Threaded Standoff - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.