## NSN 5340-01-453-9853

Angle Bracket - Page 1 of 2

Corner radius



View Online at https://aerobasegroup.com/nsn/5340-01-453-9853

Mounting Halo Types
Mounting Hole Type:
Plain
First Leg Length:
0.9000 inches
Second Leg Length:
1.9900 inches
Second Leg Width:
0.8000 inches
Second Leg Corner Radius:
0.1200 inches
First Leg Hole Diameter:
Between 0.2460 inches and 0.2520 inches
Second Leg Hole Diameter:
Between 0.2460 inches and 0.2510 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.4000 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.4000 inches
First Leg Thickness:
0.0500 inches
Second Leg Thickness:
0.0500 inches
First Leg Width:
0.8000 inches
First Leg Corner Radius:
0.2500 inches
First Leg Distance Between Hole Centers Along Width:
0.3800 inches
First Leg Distance Between First And Second Hole Centers Along Width:
0.1900 inches
First Leg Distance Between Second And Third Hole Centers Along Width:
0.1900 inches
First Leg Distance From Edge To Hole Center Along Width:
0.2100 inches
First Leg Distance From Edge To Hole Center Along Length:
0.2500 inches
First Leg Distance Between First And Second Hole Centers Along Length:
0.1900 inches
First Leg Distance Between Second And Third Hole Centers Along Length:
0.1900 inches
First Leg Style:

## **NSN 5340-01-453-9853** Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Four holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-q225/5 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.