NSN 5340-01-455-8655

Mil-a-8625 spec.

Spacing Threaded Standoff - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-455-8655 |
|--|
| Thread Class: |
| 3b left internal (includes through thread) |
| Thread Direction: |
| Right-hand left internal (includes through thread) |
| Thread Length: |
| 0.2950 inches left internal (includes through thread) |
| Diameter: |
| 0.3100 inches |
| Cross-sectional Shape: |
| Round |
| Thready Qty Per Inch (tpi): |
| 32 left internal (includes through thread) |
| Thread Size: |
| 0.1900 inches left internal (includes through thread) |
| Special Features: |
| There is a insert included made to ms2120 (table i or 304 cres per fed-std-66) |
| Material: |
| Aluminum alloy 2024 or aluminum alloy 6061 |
| Material Specification: |
| Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response or qq-a-200/8 federal |
| specification single material response or qq-a-225/8 federal specification single material response or qq-a-250/11 federal specification |
| single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 1. Cl 1 military specification single treatment response |
| Thread Series Designator: |
| Unf left internal (includes through thread) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A08900 |
| Mil-std (military Standard): |