NSN 5340-01-458-5442

Angle Bracket - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5340-01-458-5442 First Leg Length: 54.0 millimeters Second Leg Length: 230.0 millimeters Second Leg Width: 430.0 millimeters Second Leg End Width: 428.0 millimeters First Leg Hole Diameter: Between 9.2 millimeters and 9.8 millimeters Second Leg Hole Diameter: Between 9.2 millimeters and 9.8 millimeters Second Leg Distance Between First And Second Hole Centers Along Width: 185.0 millimeters Second Leg Distance Between Second And Third Hole Centers Along Width: 175.0 millimeters Second Leg Distance From Edge To Hole Center Along Width: 30.0 millimeters Second Leg Distance From Edge To Hole Center Along Length: 15.0 millimeters First Leg Thickness: 0.1345 inches Second Leg Thickness: 0.1345 inches First Leg Width: 290.0 millimeters First Leg End Width: 278.0 millimeters First Leg Distance Between First And Second Hole Centers Along Width: 165.0 millimeters First Leg Distance Between Second And Third Hole Centers Along Width: 0.0850 millimeters First Leg Distance From Edge To Hole Center Along Width: 30.0 millimeters First Leg Distance From Edge To Hole Center Along Length: 18.0 millimeters First Leg Style: Chamfered ends First Leg Hole Arrangement Style: Three holes

Second Leg Style:

Chamfered ends

NSN 5340-01-458-5442 Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
Three holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
6.4 radians
First Leg Chamfer Angle:
Between 44.0 radians and 46.0 radians
Second Leg Chamfer Angle:
Between 44.0 degrees and 46.0 degrees
Material:
Steel comp 1009
Material Specification:
Astm-a-366 assn standard single material response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A042a0