

View Online at <https://aerobasegroup.com/nsn/5340-01-458-5899>

First Leg Length:

Between 0.7200 inches and 0.7800 inches

Second Leg Length:

Between 1.7400 inches and 1.8000 inches

Second Leg Width:

Between 2.0300 inches and 2.0900 inches

Second Leg End Width:

Between 1.1900 inches and 1.2500 inches

First Leg Hole Diameter:

Between 0.1100 inches and 0.1300 inches

Second Leg Hole Diameter:

Between 0.9700 inches and 1.0300 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.7900 inches and 0.8400 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.7800 inches and 0.8400 inches

First Leg Thickness:

0.0600 inches

Second Leg Thickness:

0.0600 inches

First Leg Width:

Between 1.4700 inches and 1.5300 inches

First Leg Distance Between Hole Centers Along Width:

1.0000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.2400 inches and 0.2600 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.2400 inches and 0.2600 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.24 radians and 0.26 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.