

View Online at <https://aerobasegroup.com/nsn/5340-01-458-5899>

**First Leg Length:**

Between 0.7200 inches and 0.7800 inches

**Second Leg Length:**

Between 1.7400 inches and 1.8000 inches

**Second Leg Width:**

Between 2.0300 inches and 2.0900 inches

**Second Leg End Width:**

Between 1.1900 inches and 1.2500 inches

**First Leg Hole Diameter:**

Between 0.1100 inches and 0.1300 inches

**Second Leg Hole Diameter:**

Between 0.9700 inches and 1.0300 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.7900 inches and 0.8400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.7800 inches and 0.8400 inches

**First Leg Thickness:**

0.0600 inches

**Second Leg Thickness:**

0.0600 inches

**First Leg Width:**

Between 1.4700 inches and 1.5300 inches

**First Leg Distance Between Hole Centers Along Width:**

1.0000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.2400 inches and 0.2600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.2400 inches and 0.2600 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.24 radians and 0.26 radians

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.