NSN 5340-01-458-5951

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-458-5951

First Leg Length:

Between 0.7300 inches and 0.8500 inches

Second Leg Length:

Between 1.1900 inches and 1.3100 inches

Second Leg Width:

Between 7.6500 inches and 7.7700 inches

First Leg Hole Diameter:

Between 0.3560 inches and 0.3680 inches

First Leg Thickness:

0.0900 inches

Second Leg Thickness:

0.0900 inches

Center Section Height:

Between 2.2800 inches and 2.3400 inches

Center Section Width:

Between 14.5900 inches and 14.8300 inches

Center Section Thickness:

0.0900 inches

First Leg Width:

9.4600 inches

First Leg Distance Between Hole Centers Along Width:

2.2500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.6250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.8530 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.22 radians and 0.28 radians

Second Leg Angle:

Between 0.22 radians and 0.28 radians

Material:

Aluminum alloy 6061

NSN 5340-01-458-5951

Double Angle Bracket - Page 2 of 2

A042a0

Mil-std-171 spec.

Mil-std (military Standard):



Material Specification:
Qq-a-250/11 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-std-171, 7.3.1 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiiq: