

View Online at <https://aerobasegroup.com/nsn/5340-01-458-5968>

First Leg Length:

0.5100 inches

Second Leg Length:

0.7200 inches

First Leg Hole Diameter:

Between 0.1410 inches and 0.2350 inches

Second Leg Hole Diameter:

Between 0.2410 inches and 0.2430 inches

Second Leg Distance Between Hole Centers Along Width:

2.2850 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.9140 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.9140 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.1900 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.3080 inches

First Leg Thickness:

0.0900 inches

Second Leg Thickness:

0.0900 inches

First Leg Width:

3.5600 inches

First Leg End Width:

3.4400 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.8260 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.9880 inches

First Leg Distance From Edge To Hole Center Along Width:

0.1620 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2410 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.06 radians

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-20/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.