## NSN 5340-01-458-7835

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-458-7835 First Leg Length: 2.0000 inches Second Leg Length: 2.3100 inches Second Leg Width: 2.0000 inches First Leg Hole Diameter: Between 0.2500 inches and 0.2800 inches Second Leg Hole Diameter: Between 0.1180 inches and 0.1530 inches Second Leg Distance Between Hole Centers Along Width: 1.1560 inches Second Leg Distance Between Hole Centers Along Length: 1.1560 inches Second Leg Distance From Edge To Hole Center Along Width: 0.4220 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.4220 inches First Leg Thickness: 0.3800 inches **Second Leg Thickness:** 0.3800 inches **Center Section Height:** 3.9000 inches **Center Section Width:** 2.0000 inches **Center Section Thickness:** 0.3800 inches First Leg Width: 2.0000 inches First Leg Distance Between Hole Centers Along Width: 1.0000 inches First Leg Distance Between Hole Centers Along Length: 1.0000 inches First Leg Distance From Edge To Hole Center Along Width: 0.5000 inches First Leg Distance From Edge To Hole Center Along Length: 0.5000 inches First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

## NSN 5340-01-458-7835

Double Angle Bracket - Page 2 of 2



Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Four holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
0.25 radians
Second Leg Angle:
0.25 radians
Material:
Aluminum alloy 5083 or aluminum alloy 5086
Material Specification:
Qq-a-250/7 federal specification single material response or qq-a-250/6 federal specification single material response or qq-a-200/4 federal
specification single material response or qq-a-200/5 federal specification single material response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A042a0