NSN 5340-01-458-8026

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-458-8026

First Leg Length:

0.6200 inches

Second Leg Length:

0.6200 inches

Second Leg Width:

4.1800 inches

First Leg Hole Diameter:

Between 0.1790 inches and 0.1850 inches

Second Leg Hole Diameter:

Between 0.1790 inches and 0.1850 inches

Second Leg Distance Between Hole Centers Along Width:

2.3800 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.2000 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.2400 inches and 0.2600 inches

First Leg Thickness:

Between 0.0760 inches and 0.0840 inches

Second Leg Thickness:

Between 0.0760 inches and 0.0840 inches

Center Section Height:

4.7100 inches

Center Section Width:

4.1800 inches

Center Section Thickness:

Between 0.0760 inches and 0.0840 inches

First Leg Width:

3.1800 inches

First Leg Distance Between Hole Centers Along Width:

2.4000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.3800 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.2400 inches and 0.2600 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

NSN 5340-01-458-8026

Double Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
0.09 radians
Second Leg Angle:
0.09 radians
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541, cl 3 military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-5541 spec.