NSN 5340-01-458-8026

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-458-8026

First Leg Length: 0.6200 inches Second Leg Length: 0.6200 inches Second Leg Width: 4.1800 inches
Second Leg Length: 0.6200 inches Second Leg Width:
0.6200 inches Second Leg Width:
Second Leg Width:
-
4.1800 inches
First Leg Hole Diameter:
Between 0.1790 inches and 0.1850 inches
Second Leg Hole Diameter:
Between 0.1790 inches and 0.1850 inches
Second Leg Distance Between Hole Centers Along Width:
2.3800 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.2000 inches
Second Leg Distance From Edge To Hole Center Along Length:
Between 0.2400 inches and 0.2600 inches
First Leg Thickness:
Between 0.0760 inches and 0.0840 inches
Second Leg Thickness:
Between 0.0760 inches and 0.0840 inches
Center Section Height:
4.7100 inches
Center Section Width:
4.1800 inches
Center Section Thickness:
Between 0.0760 inches and 0.0840 inches
First Leg Width:
3.1800 inches
First Leg Distance Between Hole Centers Along Width:
2.4000 inches
First Leg Distance From Edge To Hole Center Along Width:
0.3800 inches
First Leg Distance From Edge To Hole Center Along Length:
Between 0.2400 inches and 0.2600 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Square Second Leg Hole Arrangement Style:

NSN 5340-01-458-8026

Double Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg: Not identical First Leg Angle: 0.09 radians Second Leg Angle: 0.09 radians Material: Aluminum alloy 5052 **Material Specification:** Qq-a-250/8 federal specification single material response Surface Treatment: Chromate Surface Treatment Specification: Mil-c-5541, cl 3 military specification single treatment response **Style Designator:** Adjacent angles Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A042a0 Mil-std (military Standard): Mil-c-5541 spec.
