

View Online at <https://aerobasegroup.com/nsn/5340-01-458-8580>

**First Leg Length:**

0.5500 inches

**Second Leg Length:**

0.8500 inches

**Second Leg Width:**

2.2600 inches

**First Leg Hole Diameter:**

Between 0.1190 inches and 0.1240 inches

**Second Leg Hole Diameter:**

Between 0.1190 inches and 0.1240 inches

**Second Leg Distance Between First And Second Hole Centers Along Width:**

1.1000 inches

**Second Leg Distance Between Second And Third Hole Centers Along Width:**

1.1000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.3000 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.1500 inches

**First Leg Thickness:**

0.3000 inches

**Second Leg Thickness:**

0.2500 inches

**First Leg Width:**

2.8000 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.1000 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.1000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.3000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.1200 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.