

View Online at <https://aerobasegroup.com/nsn/5340-01-459-1345>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.9700 inches and 2.0000 inches

Second Leg Length:

Between 0.1970 inches and 2.0000 inches

Second Leg Width:

Between 1.7200 inches and 1.7500 inches

First Leg Hole Diameter:

Between 0.4400 inches and 0.4600 inches

Second Leg Hole Diameter:

Between 0.1920 inches and 0.1960 inches

Second Leg Distance Between Hole Centers Along Width:

1.0000 inches

Second Leg Distance Between Hole Centers Along Length:

1.0000 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.3600 inches and 0.3800 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.3600 inches and 0.3800 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

Between 1.7200 inches and 1.7500 inches

First Leg Corner Radius:

Between 0.3600 inches and 0.3800 inches

First Leg Distance Between Hole Centers Along Width:

0.5000 inches

First Leg Distance Between Hole Centers Along Length:

0.6500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.3600 inches and 0.3800 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.4900 inches and 0.5000 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.15 radians and 0.25 radians

Material:

Aluminum alloy 6061

Material Specification:

Astm-b-308 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171, finish 7.3.1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.