

View Online at <https://aerobasegroup.com/nsn/5340-01-459-1362>

**First Leg Length:**

Between 0.1970 inches and 2.0000 inches

**Second Leg Length:**

Between 0.1970 inches and 2.0000 inches

**Second Leg Width:**

Between 1.7200 inches and 1.7500 inches

**First Leg Hole Diameter:**

Between 0.4400 inches and 0.4600 inches

**Second Leg Hole Diameter:**

Between 0.1920 inches and 0.1960 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.0000 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.0000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.3600 inches and 0.3800 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.3600 inches and 0.3800 inches

**First Leg Thickness:**

0.2500 inches

**Second Leg Thickness:**

0.2500 inches

**First Leg Width:**

Between 1.7200 inches and 1.7500 inches

**First Leg Corner Radius:**

Between 0.3600 inches and 0.3800 inches

**First Leg Distance Between Hole Centers Along Width:**

0.5000 inches

**First Leg Distance Between Hole Centers Along Length:**

0.6500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.4900 inches and 0.5000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.4900 inches and 0.5000 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.15 radians and 0.25 radians

**Material:**

Aluminum alloy 6061

**Material Specification:**

Astm-b-308 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171, finish 7.3.1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.