## NSN 5340-01-459-4083



Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-459-4083 First Leg Length: 0.5000 inches Second Leg Length: 0.7500 inches First Leg Hole Diameter: 0.1380 inches Second Leg Hole Diameter: 0.1120 inches Second Leg Distance Between Hole Centers Along Width: Between 7.8410 inches and 7.8470 inches Second Leg Distance Between First And Second Hole Centers Along Width: Between 1.8250 inches and 1.8310 inches Second Leg Distance Between Second And Third Hole Centers Along Width: 4.1880 inches First Leg Thickness: 0.0900 inches Second Leg Thickness: 0.1090 inches First Leg Width: 8.3800 inches First Leg Distance Between Hole Centers Along Width: 7.2750 inches First Leg Distance Between First And Second Hole Centers Along Width: 1.8750 inches First Leg Distance Between Second And Third Hole Centers Along Width: 3.2500 inches First Leg Distance From Edge To Hole Center Along Length: 0.2690 inches First Leg Style: Chamfered ends First Leg Hole Arrangement Style: Four holes Second Leg Style: Cut out Second Leg Hole Arrangement Style: Four holes Second Leg Relationship To First Leg: Not identical First Leg Angle:

0.60 radians

First Leg Cutout Length:

1.5400 inches

## **NSN 5340-01-459-4083** Angle Bracket - Page 2 of 2



First Leg Chamfer Angle:
45.0 radians
Material:
Steel comp 304
Material Specification:
Qq-s-763, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0