

View Online at <https://aerobasegroup.com/nsn/5340-01-459-7484>

First Leg Length:

Between 2.9700 inches and 3.0300 inches

Second Leg Length:

Between 6.1200 inches and 6.1800 inches

Second Leg Width:

Between 3.6000 inches and 3.6400 inches

Second Leg End Width:

0.3200 inches

First Leg Hole Diameter:

Between 1.4800 inches and 1.5200 inches

Second Leg Hole Diameter:

Between 0.3700 inches and 0.3900 inches

Second Leg Distance Between Hole Centers Along Width:

0.5600 inches

Second Leg Distance Between Hole Centers Along Length:

2.9800 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.5600 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.7600 inches

First Leg Thickness:

0.1250 inches

Second Leg Thickness:

0.1250 inches

First Leg Width:

Between 3.9700 inches and 4.0300 inches

First Leg End Width:

2.5000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.0000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.1250 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.35 radians and 0.41 radians

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

, ilstd-171, fin. 7.3.1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.