

View Online at <https://aerobasegroup.com/nsn/5340-01-460-0709>

**First Leg Length:**

Between 2.1400 inches and 2.2400 inches

**Second Leg Length:**

Between 5.2000 inches and 5.3000 inches

**Second Leg Width:**

2.8900 inches

**First Leg Hole Diameter:**

Between 0.3540 inches and 0.3680 inches

**Second Leg Hole Diameter:**

Between 0.2180 inches and 0.2320 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.5000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.6930 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.3500 inches

**First Leg Thickness:**

0.9000 inches

**Second Leg Thickness:**

0.9000 inches

**First Leg Width:**

5.0500 inches

**First Leg End Width:**

4.5500 inches

**First Leg Distance Between Hole Centers Along Width:**

3.7500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.6500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.7500 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 0.47 radians and 0.53 radians

**First Leg Chamfer Angle:**

45.0 degrees

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171, 7.3.1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.