

View Online at <https://aerobasegroup.com/nsn/5340-01-460-0709>

First Leg Length:

Between 2.1400 inches and 2.2400 inches

Second Leg Length:

Between 5.2000 inches and 5.3000 inches

Second Leg Width:

2.8900 inches

First Leg Hole Diameter:

Between 0.3540 inches and 0.3680 inches

Second Leg Hole Diameter:

Between 0.2180 inches and 0.2320 inches

Second Leg Distance Between Hole Centers Along Width:

1.5000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.6930 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.3500 inches

First Leg Thickness:

0.9000 inches

Second Leg Thickness:

0.9000 inches

First Leg Width:

5.0500 inches

First Leg End Width:

4.5500 inches

First Leg Distance Between Hole Centers Along Width:

3.7500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.6500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.7500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.47 radians and 0.53 radians

First Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 6061

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171, 7.3.1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.