

View Online at <https://aerobasegroup.com/nsn/5340-01-460-1092>

**First Leg Length:**

1.3500 inches

**Second Leg Length:**

1.0650 inches

**Second Leg Width:**

5.1200 inches

**Second Leg End Width:**

4.8800 inches

**First Leg Slot Length:**

0.3800 inches

**First Leg Slot Width:**

Between 0.2190 inches and 0.2230 inches

**Second Leg Hole Diameter:**

Between 0.1280 inches and 0.2230 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.4060 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.3600 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.4400 inches

**First Leg Thickness:**

0.1250 inches

**Second Leg Thickness:**

0.1250 inches

**First Leg Width:**

5.1200 inches

**First Leg End Width:**

4.8800 inches

**First Leg Distance Between Hole Centers Along Width:**

4.3750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.3725 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.2900 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.25 radians

**First Leg Chamfer Angle:**

Between 43.0 degrees and 47.0 degrees

**Second Leg Chamfer Angle:**

Between 43.0 degrees and 47.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-s-td-171, fin. 7.3.3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-td-171 spec.