NSN 5340-01-460-2385

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-460-2385
Thread Class:
2b left internal (includes through thread)
Thread Direction:
Right-hand left internal (includes through thread)
Thread Length:
0.3750 inches left internal (includes through thread)
Diameter:
0.3125 inches
Length:
0.3750 inches
Cross-sectional Shape:
Round
Thready Qty Per Inch (tpi):
32 left internal (includes through thread)
Thread Size:
0.1380 inches left internal (includes through thread)
Right Projection Diameter:
Between 0.2450 inches and 0.2490 inches
Right Projection Length:
0.1650 inches
Material:
Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or steel
comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 420f or steel comp 420fse or steel comp 430f
Material Specification:
Astm-a-581 assn standard single material response or astm-a-582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Style Designator:
Projection one end
Thread Series Designator:
Unc left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No No
Fiig:
A08900

Mil-f-14072 spec.

Mil-std (military Standard):