

View Online at <https://aerobasegroup.com/nsn/5340-01-460-2407>

First Leg Length:

Between 2.1300 inches and 2.2500 inches

Second Leg Length:

Between 3.6900 inches and 3.8100 inches

Second Leg Width:

Between 4.9600 inches and 5.0600 inches

Second Leg End Width:

2.8900 inches

First Leg Hole Diameter:

Between 0.3540 inches and 0.3700 inches

Second Leg Hole Diameter:

Between 0.2180 inches and 0.2320 inches

Second Leg Distance Between Lower Hole Centers Along Width:

1.5000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.6910 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.3450 inches

First Leg Thickness:

0.1900 inches

Second Leg Thickness:

0.1900 inches

First Leg Width:

Between 4.9600 inches and 5.0600 inches

First Leg End Width:

4.5000 inches

First Leg Distance Between Hole Centers Along Width:

3.7500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.6500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.7500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 0.47 radians and 0.53 radians

Material:

Aluminum alloy 6061

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-std-171, fin. 7.3.1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.