

View Online at <https://aerobasegroup.com/nsn/5340-01-463-0304>

First Leg Length:

0.7500 inches

Second Leg Length:

0.7500 inches

Second Leg Width:

17.0000 inches

First Leg Slot Length:

0.3750 inches

First Leg Slot Width:

0.1870 inches

Second Leg Hole Diameter:

Between 0.2210 inches and 0.2260 inches

Second Leg Distance Between Hole Centers Along Width:

3.3120 inches

Second Leg Distance From Edge To Hole Center Along Width:

6.8400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Thickness:

0.0940 inches

Second Leg Thickness:

0.0940 inches

First Leg Width:

17.0000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.7500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

6.2500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.7500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.2500 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

4.5000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

4 slots

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

0.5000 inches

Second Leg Cutout Width:

2.5000 inches

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.