**NSN 5340-01-463-6101**Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-463-6101
Thread Class:
3b left internal (includes through thread)
Thread Direction:
Right-hand left internal (includes through thread)
Thread Length:
0.6050 inches and 0.6450 inches left internal (includes through thread)
Flange Diameter:
0.7500 inches
Flange Thickness:
0.1000 inches
Diameter:
0.3100 inches
Length:
0.5250 inches
Cross-sectional Shape:
Round
Thready Qty Per Inch (tpi):
32 left internal (includes through thread)
Thread Size:
0.190 inches left internal (includes through thread)
Material:
Aluminum alloy 2024 or aluminum alloy 6061
Material Specification:
Qq-a-200/3 federal specification single material response or qq-a-225/8 federal specification single material response or qq-a-200/8 federa
specification single material response or qq-a-225/8 federal specification single material response or qq-a-225/6 federal specification single
material response or qq-a-250/4 federal specification single material response or qq-a-200/3 federal specification single material response
or qq-a-250/11 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1, cl 1 military specification single treatment response
Style Designator:
Flanged
Thread Series Designator:
Unf left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

Mil-std (military Standard):

A08900