

View Online at <https://aerobasegroup.com/nsn/5340-01-464-2475>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.2500 inches

**Second Leg Length:**

1.7500 inches

**Second Leg Width:**

1.5000 inches

**Second Leg End Width:**

0.7000 inches

**First Leg Hole Diameter:**

Between 0.2500 inches and 0.3360 inches

**Second Leg Hole Diameter:**

Between 0.7000 inches and 0.7100 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.7500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.7000 inches

**First Leg Thickness:**

0.1250 inches

**Second Leg Thickness:**

0.1250 inches

**First Leg Width:**

1.5000 inches

**First Leg End Width:**

1.0000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.7500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.4000 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.25 radians

**First Leg Chamfer Angle:**

0.25 radians

**Second Leg Chamfer Angle:**

40.0 radians

**Material:**

Aluminum alloy 5086 or aluminum alloy 5052

**Material Specification:**

Qq-a-250/7 federal specification single material response or astm-b-209 assn standard single material response or qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.