

View Online at <https://aerobasegroup.com/nsn/5340-01-465-0344>

First Leg Length:

3.3800 inches

Second Leg Length:

5.0000 inches

Second Leg Width:

2.5000 inches

Second Leg Corner Radius:

0.1200 inches

First Leg Slot Length:

Between 0.9700 inches and 1.0300 inches

First Leg Slot Width:

Between 0.4200 inches and 0.4290 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.2500 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.2800 inches

Second Leg Slot Length:

Between 0.9700 inches and 1.0300 inches

Second Leg Slot Width:

Between 0.3750 inches and 0.3820 inches

First Leg Thickness:

0.2500 inches

Second Leg Thickness:

0.2500 inches

First Leg Width:

2.5000 inches

First Leg Corner Radius:

0.1200 inches

First Leg Distance From Edge To Hole Center Along Width:

1.2500 inches

First Leg Distance From Edge To Hole Center Along Length:

1.2550 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.50 radians

Material:

Steel comp 1026 or steel comp 1029 or steel comp 1030 or steel

Material Specification:

Astm-a-36 assn standard single material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-std-171, finish 5.1.1 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-std-171 spec.